



50068005

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

1. IDENTIFICATION**Product identifier****Product name** KLEENMOLD 202**Other means of identification****Product Code(s)** 083381**Number** JJE
Substance/mixture Mixture**Recommended use of the chemical and restrictions on use****Identified uses** Lubricant. Industrial applications .**Uses advised against** Do not use for any purpose other than the one for which it is intended**Details of the supplier of the safety data sheet****Supplier Address** TOTAL Specialties USA, Inc.
1201 Louisiana St. Suite 1800
Houston, TX 77002
Phone: 713-483-5000**Contact Point** Technical/ HSEQ**E-mail Address** USRMLIN-info@total.com**Emergency telephone number****Company Phone Number****Emergency telephone**

+1 (908) 862-9300

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic)

1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

2. HAZARDS IDENTIFICATION**Classification**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version GNAM



SDS #: 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Hazards not otherwise classified (HNOC)

None known

Other information**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.

Environmental properties

The product may form an oil film on the water surface that may stop the oxygen exchange. Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture****Chemical nature**

Mineral oil of petroleum origin.

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	30-<40
Sulfur	7704-34-9	1-<3

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

** The exact percentage (concentration) of composition has been withheld as a trade secret***4. FIRST AID MEASURES****First aid measures for different exposure routes****General advice**

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.

Inhalation

Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.

Ingestion

Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Protection of First-aiders

First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Skin contact	Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO ₂ and SO ₃) and Hydrogen sulphide H ₂ S, Mercaptans, Silicon dioxide.

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

<u>Protective Equipment and Precautions for Firefighters</u>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.
---	--

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
----------------------------	--

Version GNAM



SDS #: 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Other information

See Section 12 for additional information.

Environmental precautions**General Information**

Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up**Methods for containment**

Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.

Methods for cleaning up

Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion

Take precautionary measures against static discharges.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure limits**

Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Exposure controls**Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment**General Information**

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.

Eye/face protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots.

Hand Protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection

None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties****Appearance****Color****Physical State @20°C****Odor**

paste

black

Paste/Gel

Characteristic

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Odor Threshold

No information available

Property**Values****Remarks****Method**

pH

Not applicable

Melting point/range

No information available

Boiling point/boiling range

No information available

Flash point

>= 160 °C

>= 320 °F

Cleveland Open Cup (COC)
ASTM D 92
Cleveland Open Cup (COC).
ASTM D 92.

Evaporation rate

< 1 (n-Butyl acetate=1) @ 25 °C

Flammability Limits in Air

No information available

upper

-

No information available

Lower

-

No information available

Vapor Pressure

< 0.15 hPa

@ 38 °C

Vapor density

> 8

(Air = 1)

Relative density

0.96

@ 25 °C

Density

0.96 g/cm3

@ 25 °C

Water solubility

Insoluble

Solubility in other solvents

Soluble in many common
organic solvents

logPow

No information available

Autoignition temperature

Not applicable

Decomposition temperature

No information available

Viscosity, kinematic

Not applicable

Explosive properties

Not explosive

Oxidizing Properties

No information available

Possibility of hazardous reactions

See section 10

Other information

Freezing Point

No information available

Note

• Please refer to Technical Data Sheet for further information

10. STABILITY AND REACTIVITY**Reactivity**

No information available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks. Take precautionary measures against static discharges.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Silicon dioxide.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Principle Routes of Exposure**

Inhalation, Ingestion, Eye contact, Skin contact.

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Skin contact

Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

Eye contact

Not classified.

Inhalation

Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion

Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information****Product Information**

Product does not present an acute toxicity hazard based on known or supplied information.

Oral

Not classified based on available data

Dermal

Not classified based on available data

Inhalation

Not classified based on available data

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	
Sulfur 7704-34-9	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.43 mg/L (Rat) 4 h

Skin corrosion/irritation

Not classified based on available data.

Serious eye damage/eye irritation

Not classified based on available data.

Sensitization

Not classified as a sensitizer.

Carcinogenicity

This product is not classified carcinogenic.

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

OSHA: (Occupational Safety & Health Administration) X - Present

Mutagenicity	This product is not classified as mutagenic.
Reproductive toxicity	This product does not present any known or suspected reproductive hazards.
Target Organ Effects (STOT)	None known.
STOT - single exposure	Not classified based on available data.
STOT - repeated exposure	Not classified based on available data.
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).
Aspiration hazard	Not classified based on available data.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	EC50 (48h) > 1000 mg/L Daphnia magna	
Sulfur 7704-34-9		-		

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Version GNAM



SDS #: 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Component Information No information available.**Mobility**

Soil Given its physical and chemical characteristics, the product has no soil mobility.
Air Loss by evaporation is limited
Water The product is insoluble and floats on water
Other adverse effects

General Information No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

California Hazardous Waste Codes 221

14. TRANSPORT INFORMATION**DOT** Not regulated**ICAO/IATA** Not regulated**IMDG/IMO** Not regulated**ADR/RID** Not regulated**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)
Canada (DSL/NDL)
Australia (AICS)
Korea (KECL)

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

China (IECSC)
Philippines (PICCS)
New Zealand (NZIoC)
Taiwan (TCSI)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	X			

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version GNAM



SDS # : 083381

KLEENMOLD 202

Date of the previous version: 2017-07-17

Revision Date: 2019-04-08

Version 2.04

Asphalt 8052-42-4	X	X	X	X
Graphite 7782-42-5	X	X	X	
Sulfur 7704-34-9	X	X	X	

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Special hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2019-04-08

Revision Note *** Indicates updated section

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend**Section 8**

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDLH - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

Version GNAM